

SPECIALIZED TECH INC.
Gas Well Desanding Services



English Units

Unit	ANSI Rating	MAWP (psi)	MDMT (°F)	Designated Service	Sand Capacity (lb)	Liquid Capacity (bbl)	Nominal Gas Capacity (mmcfpd @ 1000psi;100 mesh sand)*	Inlet configuration	Weight (lb)Empty	Length (ft)	Other
2810	600	1,440	-20	Sweet	132	0.2	9.5	2" Threaded	2,541	13.5	
2815	600	1,440	-20	Sweet	185	0.4	11.8	2" Threaded	2,860	22.3	
21615	600	1,480	-50	Sour	1,270	2.3	30.6	4" Flanged	5,533	22.3	
21620	600	1,480	-50	Sour	1,732	3.1	44.7	4" Flanged	6,578	27.2	
41210	1500	2,900	-50	Sour	298	0.6	13.7	2"3" Threaded/flanged	3,542	16.1	insulated
41215	1500	2,900	-50	Sour	476	0.9	22.2	2"3" Threaded/flanged	4,378	22.3	insulated
41220	1500	2,900	-50	Sour	657	1.2	30.3	3" Flanged	5,830	27.2	
52420	1500	3,705	-20	Sour	2,649	4.9	63.3	3" Flanged	21,500	23.6	insulated
52420 M	1500	3,705	-20	Sour	1,411	2.6	73.2	8" Flanged	21,000	23.6	insulated
61416	2500	6,180	-50	Sour	602	1.1	25.9	3" Flanged	10,000	16.0	

* NOTE: piping geometry on location may prevent achieving design capacities.