

SPECIALIZED TECH INC.
Gas Well Desanding Services



Metric Units

Unit	ANSI Rating	MAWP (kPa)	MDMT (°C)	Designated Service	Sand Capacity (kg)	Liquid Capacity (L)	Nominal Gas Capacity (e ³ m ³ /d @ 7000kPa;100 mesh sand)*		Weight (kg)Empty	Length (m)	Other
								Inlet configuration			
2810	600	9,900	-29	Sweet	60	37	268	2" Threaded	1,155	4.1	
2815	600	9,900	-29	Sweet	84	56	335	2" Threaded	1,300	6.8	
21615	600	10,200	-44	Sour	576	362	867	4" Flanged	2,515	6.8	
21620	600	10,200	-44	Sour	786	485	1,265	4" Flanged	2,990	8.3	
41210	1500	19,995	-44	Sour	135	93	389	2"3" Threaded/flanged	1,610	4.9	insulated
41215	1500	19,995	-44	Sour	216	140	629	2"3" Threaded/flanged	1,990	6.8	insulated
41220	1500	19,995	-44	Sour	298	188	857	3" Flanged	2,650	8.3	
52420	1500	25,545	-29	Sour	1,202	782	1,793	3" Flanged	9,750	7.2	insulated
52420 M	1500	25,545	-29	Sour	640	416	2,072	8" Flanged	9,500	7.2	insulated
61416	2500	42,450	-44	Sour	273	171	733	3" Flanged	4,525	4.9	

* NOTE: piping geometry on location may prevent achieving design capacities.